



Vehicle description for: TGS 33.400 6x4 BB CH



Illustration can deviate

Vehicle standards

Product family	The new MAN Truck Generation
Model & Variant	TGS 33.400 6x4 BB CH
Vehicle type	Vehicle type, platform truck and chassis (LK)
Cab	Local transport cab NN
Main wheel distance	4500 mm
Overhang	2500 mm
Steering configuration	Left

Vertical Load

	National Registration	Technical Load	Technical Load Plus
Gross weight	28,000 kg	32,500 kg	32,500 kg
Front axle	8,000 kg	8,000 kg	8,000 kg
Rear axle	10,000 kg	13,000 kg	13,000 kg
Rear axle 2	10,000 kg	13,000 kg	13,000 kg

Horizontal Load

	National Registration	Technical Load	Technical Load Plus
Gross train weight	0 kg	0 kg	0 kg



The printed images in this offer are for explanatory purposes and may differ from the actual configuration.
For further product information on the tire selection "selectively", please contact our sales staff.

Vehicle characteristics

Basic characteristics

<input type="checkbox"/>	Chassis	0P2U9
<input type="checkbox"/>	Chassis class, heavy	0P2UC
<input type="checkbox"/>	Merchant tonnage 33 t	0P8LK
<input type="checkbox"/>	Basic layout of vehicle, all-round	0PGCU
<input type="checkbox"/>	Frame type, medium-high	0P2TQ
<input type="checkbox"/>	Vehicle type, platform truck and chassis (LK)	0P2UQ
<input type="checkbox"/>	Left-hand-drive	0P3AS
<input type="checkbox"/>	Right-hand traffic	0P3F5
<input type="checkbox"/>	Vehicle documentation in Portuguese	0P2LN
<input type="checkbox"/>	Labelling in Portuguese	0P8NQ
<input type="checkbox"/>	Cab position 640 mm (distance from frame lower edge to cab floor)	0PHBE

Registration

<input type="checkbox"/>	Vehicle approval, N3G class	0P3JS
<input type="checkbox"/>	Maximum speed limiter, 85 km/h, electronic, engine speed regulation	0P2UI
<input type="checkbox"/>	Maximum vehicle noise level, 80 dB in acc. with UN/ECE-R 51.02	0PINC
<input type="checkbox"/>	Height over cab, unloaded up to 4,000 mm	0PHA1
<input type="checkbox"/>	Maximum vehicle width of 2,500 mm checked with respect to relevant chassis components	0PIOJ
<input type="checkbox"/>	Vehicle classification in accordance with regulation (EU) 2018/858	0PKAW

Documents

<input type="checkbox"/>	Data confirmation, international	0P3AO
<input type="checkbox"/>	Supplier declaration	0P3AU
<input type="checkbox"/>	European standard exhaust emission confirmation	0P2Q7
<input type="checkbox"/>	Confirmation of year of manufacture	0P2TT
<input type="checkbox"/>	Body manufacturer information sheet	0P2TN
<input type="checkbox"/>	Without registration documentation, national	0P3B0

Application scope / transport tasks

<input type="checkbox"/>	Concrete	0P6WK
<input type="checkbox"/>	102 Concrete pump	0P2R3
<input type="checkbox"/>	Temperature range, vehicle deployment, warm country	0PHIB
<input type="checkbox"/>	Case hardness of final drive Distribution	0P4F0

Lines, editions and packages

<input type="checkbox"/>	Special request paintwork	0PJTD
<input type="checkbox"/>	Without Individual Lion package	0PJT1

Horizontal and vertical loads

<input type="checkbox"/>	28,000 kg permitted gross load, vertical, nat. appr.	0P5P9
<input type="checkbox"/>	32,500 kg permitted gross load, vertical, tech.	0P5T9
<input type="checkbox"/>	32,500 kg permitted gross load, vertical, tech. Plus	0P8HY
<input type="checkbox"/>	8,000 kg permitted load on front axle, nat. appr.	0P5KT
<input type="checkbox"/>	8,000 kg permitted load on front axle, tech.	0P5LN



<input type="checkbox"/>	8,000 kg permitted load on front axle, tech. Plus	0P8D4
<input type="checkbox"/>	10,000 kg permitted load on rear axle NatZu	0P5GW
<input type="checkbox"/>	13,000 kg permitted load on rear axle, tech.	0P5IO
<input type="checkbox"/>	13,000 kg permitted load on rear axle, tech. Plus	0P8BY
<input type="checkbox"/>	10,000 kg permitted load on 2nd rear axle NatZu	0P5FE
<input type="checkbox"/>	13,000 kg permitted load on 2nd rear axle, tech.	0P5M9
<input type="checkbox"/>	13,000 kg permitted load on 2nd rear axle, tech. Plus	0P7TJ
<input type="checkbox"/>	0kN D value	0P8XD

Notification texts

<input type="checkbox"/>	Without note (propshaft wear)	0PJRV
--------------------------	-------------------------------	-------

Chassis

Vehicle frame (wheelbase, overhang, ...)

<input type="checkbox"/>	Main wheelbase, 4,500 mm	0P2ZW
<input type="checkbox"/>	Wheelbase between rear axles, 1,400 mm	0P3BX
<input type="checkbox"/>	Frame overhang, rear, 2,500 mm	0P3E1
<input type="checkbox"/>	Main frame side member thickness, 9.5 mm	0P0Y7
<input type="checkbox"/>	Vehicle rear, straight end of frame	0P0XT

Exhaust system, air intake

<input type="checkbox"/>	Exhaust silencer, side, left	0P1BG
<input type="checkbox"/>	Exhaust tailpipe, towards rear	0P1BQ
<input type="checkbox"/>	Air intake, behind cab, raised	0P0AY
<input type="checkbox"/>	Pre-separator for engine air intake	0P0BA

Battery cases, batteries, alternator

<input type="checkbox"/>	Battery, 12 V, 175 Ah, 2 units, maintenance free	0P0WA
<input type="checkbox"/>	Three-phase alternator 28 V, 120 A, 3,360 W, Longlife Eco	0P1BW
<input type="checkbox"/>	Medium battery box, 2 batteries	0P0WU
<input type="checkbox"/>	Battery box, left	0P0WO
<input type="checkbox"/>	Main battery switch, electric	0P0WE
<input type="checkbox"/>	Safety cut-out	0P1V2
<input type="checkbox"/>	Lockable battery box, with padlock	0P0WL

Tanks and fuel line

<input type="checkbox"/>	Fuel tank capacity 400 l, right	0P4ED
<input type="checkbox"/>	Fuel tank, right, steel	0P4GN
<input type="checkbox"/>	Tank cross-section, right, medium	0P4HE
<input type="checkbox"/>	Fuel tank cap, lockable for master key system	0P4H5
<input type="checkbox"/>	Filter screen for fuel tank filler neck	0P1EM
<input type="checkbox"/>	Fuel pre-filter position on the battery box	0PIW9

Frame attachments

<input type="checkbox"/>	Without underride protection, front	0P1FM
<input type="checkbox"/>	Without working platform	0P0VH
<input type="checkbox"/>	Without underride protection, side	0P1FG
<input type="checkbox"/>	Final cross member, with hole pattern 160 x 100 mm	0P1SB



- Without underride protection, rear 0P1FB
- Wheel chock, two units, without retaining device, delivered loose 0P6WX
- Without body attachment brackets/thrust plates 0P0X6

Pneumatic brakes, compressed-air generation, brake system

- Air compressor, 1-cylinder, 360 ccm 0P0AF
- Compressed-air treatment, pneumatically controlled 0P0AB
- Steel compressed-air tank 0P0XH
- Electronic brake system (EBS) 0P0BL
- Anti-lock braking system (ABS) 0P0BE
- Full brake assistant 0P0CM
- Without preparation for EBS Full control unit 0PHPM
- MAN EVBec high-performance engine brake, stages possible 0P0BW
- Drum brakes on front axle 0P11A
- Drum brakes on rear axle 0P115
- Drum brakes, on 2nd rear axle, with brake cylinders for increased clearance requirements (e.g. concrete pump) 0P11G
- Parking brake control, in instrument panel 0P3KG
- Parking brake, without spring-type actuator on 2nd rear axle (e.g. for concrete pump) 0P0C7
- Parking brake, on front axle(s), pneumatic, additional, exhaustible 0P0C1
- Brake lining thickness display, with brake lining wear warning 0P0BG
- Harmonisation of brake lining wear 0P0BI

Lights and acoustic signals on the chassis (rear lights, ...)

- Rear lights 0P2AQ
- Stone protection, for rear lights, guard, wide mesh 0P2AT
- Emergency braking signal, hazard light activation, automatic 0P0CG
- Acoust. Reversing warning system deactivatable when reverse gear selected 0P3CE
- Light function test 0P2AD
- Side marker lights, LED 0P2BJ

Driveline/running gear

Engine, radiator

- Diesel engine MAN D2066 LF06, 294 kW (400 hp) output, 1,900 Nm torque, Euro 2 0P6BR
- Fuel filter, for fuels up to Cleanliness Class 25 0PHII
- Fuel pre-filter, with oil separator/water trap 0P0AT
- Without torque reduction 0P0G5
- Engine dry-air filter, with safety insert 0P0B8
- Ventilation, crankcase, open 0P8PN
- Anti-noise skirt, engine 0P2E7
- Fan control for start of cooling with low coolant temperature (e.g. hot country) 0P0K5
- Reduction of dust swirl through radiator fan 0P1YE
- Engine cooler, normal length 0P4XX
- Radiator protection, lower 0P1XE
- Front radiator protection, grille 0P1VP
- Engine oil dipstick and digital oil level gauge 0P0B6
- Warning message for engine coolant level, with advance warning 0P0KA



<input type="checkbox"/>	Antifreeze, down to -32 °C	0P0AK
<input type="checkbox"/>	Flame-start system	0P0GD
<input type="checkbox"/>	Service product level indicator and intake system vacuum	0P3KT

Gearbox, clutch

<input type="checkbox"/>	Manually operated gearbox, MAN 16.25 OD	0P5VL
<input type="checkbox"/>	Gearbox for increased percentage of overrun during driving operation	0PGCL
<input type="checkbox"/>	Manual gearbox operation, single-H, group/split switch	0P3KL
<input type="checkbox"/>	Single-disc clutch, 430 mm, dry, without pre-damper spring, for use with high idling proportion	0P0DU
<input type="checkbox"/>	Gearbox heat exchanger	0P0FW

Wheels, tyres

<input type="checkbox"/>	Required tyre speed index G	0PFWA
<input type="checkbox"/>	Front axle tyres optionally 315/80R22.5 Steering-Short-haul TL (156/150 K)	0PEXS
<input type="checkbox"/>	Rim type, front axle, steel, single-part	0P0P0
<input type="checkbox"/>	Rim size, front axle, 10-hole, 9.00x22.5	0P0NI
<input type="checkbox"/>	Wheel nut cover ring, front axle	0P0PR
<input type="checkbox"/>	Rear axle tyres optionally 315/80R22.5 Drive-Road+Offroad TL (154/150 K)	0PDRX
<input type="checkbox"/>	Rim type, rear axle, steel, single-part	0P0OO
<input type="checkbox"/>	Rim size, rear axle, 10-hole, 9.00x22.5	0P0MU
<input type="checkbox"/>	Tyres for 2nd rear axle optionally 315/80R22.5 Drive-Road+Offroad TL (154/150 K)	0PEA2
<input type="checkbox"/>	Rim type, 2nd rear axle, steel, single-part	0P0PA
<input type="checkbox"/>	Rim size, 2nd rear axle, 10-hole, 9.00x22.5	0P0O7

Axles

<input type="checkbox"/>	6x4	0P3B9
<input type="checkbox"/>	Steering ratio, indirect	0P1JY
<input type="checkbox"/>	Steering oil tank with electrical measuring sensor	0P1JV
<input type="checkbox"/>	Front axle, 9,200 kg, not driven, straight, steered, not liftable	0P5EX
<input type="checkbox"/>	Mudguard, front axle	0P1AT
<input type="checkbox"/>	Splash guard mat on mudguard, front axle, longer at bottom	0P1XS
<input type="checkbox"/>	Rear axle, 13,000 kg, planetary axle with drive shaft, straight, not steered, not liftable	0P4ZM
<input type="checkbox"/>	Twin tyre on rear axle	0P1HN
<input type="checkbox"/>	Transfer mudguard, rear axle	0P1AQ
<input type="checkbox"/>	2nd rear axle, 13,000 kg, planetary axle without drive shaft, straight, not steered, not liftable	0P4Y7
<input type="checkbox"/>	Twin tyre on 2nd rear axle	0P1HW
<input type="checkbox"/>	Transfer mudguard, 2nd rear axle	0P1B6
<input type="checkbox"/>	Axle ratio, i = 4.00	0P0D2
<input type="checkbox"/>	Differential locks on driven rear axles	0P0DI
<input type="checkbox"/>	Without differential locks, front axles	0P0DL

Axle control system and suspension

<input type="checkbox"/>	Suspension type for front axles and driven rear axles, leaf/leaf (BB)	0P2YB
<input type="checkbox"/>	Leaf-spring suspension on front axle, parabolic, 3-leaf, steel	0P1JE
<input type="checkbox"/>	Leaf-spring suspension on rear axle, parabolic, 5-leaf, steel	0P1J2
<input type="checkbox"/>	Leaf-spring suspension on 2nd rear axle, parabolic, 5-leaf, steel	0P1JL
<input type="checkbox"/>	Spring load-bearing capacity front axle 9,500 kg	0P5C4
<input type="checkbox"/>	Spring load-bearing capacity of rear axle, 16,000 kg	0P5BW
<input type="checkbox"/>	Spring load-bearing capacity of 2nd rear axle, 16,000 kg	0P5C8



<input type="checkbox"/>	Shock absorbers on front axle	0P1M4
<input type="checkbox"/>	Shock absorbers on rear axle	0P1LQ
<input type="checkbox"/>	Shock absorbers on 2nd rear axle	0P1M9
<input type="checkbox"/>	Stabiliser, front axle	0P1LD
<input type="checkbox"/>	Stabiliser, rear axle	0P1LA
<input type="checkbox"/>	Stabiliser, 2nd rear axle	0P1LH
<input type="checkbox"/>	Wishbone	0P6ZR
<input type="checkbox"/>	Without trailer air suspension control	0PHN2

Cab

Cab and cab exterior

<input type="checkbox"/>	Local transport cab NN	0P2DL
<input type="checkbox"/>	Cab mount, Comfort	0P1V9
<input type="checkbox"/>	Cab tilt mechanism, manual	0P1V6
<input type="checkbox"/>	No tilting roof/sliding roof	0P1VY
<input type="checkbox"/>	Bumper, steel, 3 pieces	0P1SG
<input type="checkbox"/>	Front step, integrated, with grab option	0P1VE
<input type="checkbox"/>	Windscreen, composite safety glass, tinted	0P1X0
<input type="checkbox"/>	Sunblind, in front of windscreen	0P1WK
<input type="checkbox"/>	Wiper system for windscreen	0P1WG
<input type="checkbox"/>	Wiper activation, manual	0P1UL
<input type="checkbox"/>	Step unit, hinged	0P1V0
<input type="checkbox"/>	Central locking, no remote control	0P1WS
<input type="checkbox"/>	Vehicle key, 2 units	0P3JT
<input type="checkbox"/>	No door extension	0P1WV
<input type="checkbox"/>	Door windows, tinted	0P1WO
<input type="checkbox"/>	Door window, safety glass	0P1WM
<input type="checkbox"/>	Cab rear wall, no window	0P1VD

Lights and acoustic signals on cab exterior (headlights, horn, ...)

<input type="checkbox"/>	Without light and headlight package	0PKWU
<input type="checkbox"/>	Front headlights, H7	0P1ZN
<input type="checkbox"/>	Stone protection guard for front headlights, wide and fine mesh	0PICD
<input type="checkbox"/>	Daytime driving lights, LED	0P2BP
<input type="checkbox"/>	Fog lights, H7	0P2AH
<input type="checkbox"/>	Headlight beam regulator, manual	0P2AC
<input type="checkbox"/>	Driving-light control, manual	0P1ZF
<input type="checkbox"/>	Contour lights, LED, 2 units	0P2BS
<input type="checkbox"/>	Comfort indicator function, can be activated	0P1ZW
<input type="checkbox"/>	Turn signal lights, sides, bulb	0P1Z6
<input type="checkbox"/>	Horn, two-tone, electrical	0P1W1
<input type="checkbox"/>	Revolving beacons, LED, yellow (individual LEDs light up in cascades, revolving)	0P2BD
<input type="checkbox"/>	2 revolving beacons on cab roof, 1 right and 1 left	0P2B3
<input type="checkbox"/>	Preparation for loading area lighting	0P2A5
<input type="checkbox"/>	Without revolving beacons at the rear of the vehicle	0PJRO

Mirrors and mirror replacements



<input type="checkbox"/>	Exterior rear-view mirror, electrically adjustable	0P2CA
<input type="checkbox"/>	Mirror housing, not painted	0P2CP
<input type="checkbox"/>	Vehicle components, suitable for body width larger than 2,400 mm to 2,600 mm	0P2CT
<input type="checkbox"/>	Kerb mirror, right, electrically adjustable	0P2CG
<input type="checkbox"/>	Front mirror, mechanical adjustment	0P2CJ
<input type="checkbox"/>	Without mirror package	0PKWV

Seats

<input type="checkbox"/>	Seat covers, fabric, standard	0P2PQ
<input type="checkbox"/>	Comfort driver's seat, air-sprung	0P2P2
<input type="checkbox"/>	Driver's seat arm rests	0P2OE
<input type="checkbox"/>	Co-driver's seat, not sprung, length, height and backrest adjustment	0P2OP
<input type="checkbox"/>	Indicator, seat belt, 1st row of seats, acoustic and visual	0P8L1
<input type="checkbox"/>	Without driver's seat package	0PKXV
<input type="checkbox"/>	Without co-driver's seat package	0PKXU

Driver's workplace

<input type="checkbox"/>	Multi-function steering wheel, leather, adjustable height and angle	0P2GC
<input type="checkbox"/>	Steering wheel, with parking position	0P2GE
<input type="checkbox"/>	Steering lock	0P3JZ
<input type="checkbox"/>	Instrumentation, Basic km/h	0P3L3
<input type="checkbox"/>	Tachograph Simulation Unit (TSU), instead of tachograph	0P2KY
<input type="checkbox"/>	Tachograph, calibrated	0P2KG
<input type="checkbox"/>	Socket, cab centre, 2 units, 12 V and 24 V	0P2HX
<input type="checkbox"/>	Control panel MAN EasyControl, 2 functions, operable from outside with door open	0P3KB
<input type="checkbox"/>	Single DIN slots, 4 units, roof space, front	0P2FJ
<input type="checkbox"/>	Without storage tray next to seat	0PJRS

Cab air-conditioning system

<input type="checkbox"/>	Air-conditioning system, manual	0P2NU
<input type="checkbox"/>	Ventilation, cannot be disabled, permanent and slight excess pressure in cab (reduces dust penetration)	0P2NX
<input type="checkbox"/>	Pre-separator (cyclone filter) for interior air intake	0P2O7

Bunk area

<input type="checkbox"/>	Without bunk area package	0PKNE
--------------------------	---------------------------	-------

Cab interior

<input type="checkbox"/>	Without interior lighting package	0PKNF
<input type="checkbox"/>	Without driver's workplace package, Comfort	0PKXT
<input type="checkbox"/>	Colour scheme for interior styling, dark	0P2I6
<input type="checkbox"/>	Interior styling analogous to colour scheme	0PGBT
<input type="checkbox"/>	Windscreen roller blind, internal	0P2FE
<input type="checkbox"/>	Interior light, central	0PHA6
<input type="checkbox"/>	Reading light, 1 unit, driver's side	0P2IQ
<input type="checkbox"/>	Entry lighting	0P2IO
<input type="checkbox"/>	Door interior cladding, washable	0P2IA
<input type="checkbox"/>	Storage, instrument panel in middle section, open	0P2HK
<input type="checkbox"/>	Storage box, cab rear wall, 2 units, behind driver's and co-driver's sides	0P2F2
<input type="checkbox"/>	Grab handle, above door, internal, 2 units, 1 right and 1 left	0P2G2



- | | | |
|--------------------------|---|-------|
| <input type="checkbox"/> | Entry handles, standard | 0PHPK |
| <input type="checkbox"/> | Without stowage and storage space package | 0PKXS |

Accessories and tools

- | | | |
|--------------------------|--|-------|
| <input type="checkbox"/> | Without accessories and tools package | 0PKXA |
| <input type="checkbox"/> | Compressed-air connection, cab, with compressed-air hose and gun | 0P2FM |
| <input type="checkbox"/> | No jack | 0P3F6 |
| <input type="checkbox"/> | Vehicle toolkit | 0P2TX |
| <input type="checkbox"/> | No warning triangle | 0P3FH |
| <input type="checkbox"/> | Operator's manual in Portuguese, printed, additional | 0PINJ |

Intelligent Truck

Assistance systems

- | | | |
|--------------------------|---|-------|
| <input type="checkbox"/> | Electronic Stability Program (ESP) | 0P1TN |
| <input type="checkbox"/> | Anti-slip control (ASR) | 0P1T2 |
| <input type="checkbox"/> | Tempomat (cruise control, CC) | 0P1TR |
| <input type="checkbox"/> | Road speed limiter, adjustable, limiter (engine speed regulation) | 0P0C3 |
| <input type="checkbox"/> | Without advanced emergency braking system | 0P1U5 |
| <input type="checkbox"/> | Without driving fitness detection system | 0PHN5 |
| <input type="checkbox"/> | Without Front Detection | 0PHNA |
| <input type="checkbox"/> | Without traffic sign recognition | 0PHNE |
| <input type="checkbox"/> | Without Reversing Motion System | 0PHNV |
| <input type="checkbox"/> | Without distance warning system | 0PKA0 |

Infotainment (radio,...)

- | | | |
|--------------------------|--|-------|
| <input type="checkbox"/> | Radio preparation, 12 V | 0P2M4 |
| <input type="checkbox"/> | Loudspeaker, door, 2 units, 1 left and 1 right | 0P2ME |
| <input type="checkbox"/> | No navigation map | 0P2N2 |
| <input type="checkbox"/> | English additionally for display | 0P2JQ |

Bodies/interfaces

Interfaces to semitrailer (e.g. fifth-wheel coupling, brake connection,...)

- | | | |
|--------------------------|---|-------|
| <input type="checkbox"/> | Without trailer brake connection behind cab | 0P1O3 |
| <input type="checkbox"/> | No fifth-wheel coupling | 0P1RJ |
| <input type="checkbox"/> | Without sensing of the fifth-wheel coupling | 0PHN7 |

Interfaces to trailer (e.g. trailer coupling, brake connections,...)

- | | | |
|--------------------------|--|-------|
| <input type="checkbox"/> | Without trailer/towing coupling on final cross member | 0P1NQ |
| <input type="checkbox"/> | Without trailer brake connection at end of frame, centre | 0P1O0 |
| <input type="checkbox"/> | Without trailer socket at frame end | 0P1OW |
| <input type="checkbox"/> | Without trailer socket for anti-lock brake system (ABS) | 0P1O9 |

Ex works bodies and interfaces to bodies (e.g. tipper indicator...)

- | | | |
|--------------------------|--|-------|
| <input type="checkbox"/> | Preparation for engine start/stop facility, under front panel | 0P0K8 |
| <input type="checkbox"/> | Interface for data exch. with body (customer-specific control module) and engine intermediate speed control (ZDR), front area of cab | 0P2NA |



- Interface for vehicle data (FMS) 0P2J3

PTOs

- PTO, engine-dependent, shiftable 0P4N7
- PTO, engine-dependent, type NMV221, f=1.55 speed factor, 1,300 Nm torque continuous load 0P4WM
- Flange connection on PTO, engine-dependent, 120 mm diameter (8-hole) 0P4OT
- Engine-dependent power take-off, continuous operation 0P4XF
- Function parameters for PTO, engine-dependent, stationary operation 0P4WX
- PTO, gearbox-dependent, type NH/1c, without flange, f=0.91/1.09, position approx. 3 o'clock 0P4QF
- PTO, gearbox-dependent, continuous operation 0P4VJ
- PTO, gearbox-dependent, shiftable 0P4X9
- Without fan wheel for PTO, gearbox-dependent 0P4VR
- Function parameters for PTO, gearbox-dependent, stationary operation 0P4WO
- Gearbox shift blocking for PTO operation, pneumatic 0P4VS
- Electrical circuit for PTO, engine-dependent 0P4QN
- Sector-specific parameterisation for concrete pump vehicles (working speed control) 0P4X4

Towing, recovery and lashing

- Central coupling jaw, integrated in bumper/front cross member, with lock pin 0P1MK

Paintworks

Paintwork, cab, top

- Top coating, cab 0P6YB

Paintwork, cab, bottom

- Textured coating, step units 0P6X9
- Textured coating, mudguard, behind cab 0P6YG
- Textured coating, bumper, steel 0P6YQ

Paintwork, chassis

- Top coating, chassis 0P6YC
- Top coating, rims, steel, white-aluminium 0P6YL

Colour

- Top coating, cab PURE WHITE RAL 9010 N
- Top coating, chassis GRAPHITE BLACK RAL 9011 W



Technical data: TGS 33.400 6x4 BB CH / L26EAA06

<u>Vehicle type: Vehicle type, platform truck and chassis (LK)</u>	
<u>Cab: Local transport cab NN</u>	
<u>Drive Type: 6x4</u>	
Lengths mm	
TD071	Total length 10007.0
TD063	Front vehicle overhang 1607.0
TD057	Wheelbase between front axles 0
TD058	Wheelbase between leading axle and rear axle 0
TD059	Wheelbase between rear axles 1400
TD060	Wheelbase between rear axle and trailing axle 0
TD064	Rear frame overhang 2500.0
TD072	Distance from first front axle to body 465.0
TD067	Distance to kingpin from front axle, nominal position -
TD074	Slew radius, front -
TD075	Slew radius, rear -
TD068	Coupling length -
Widths mm	
TD008	Width included rearview mirror 2981.0
TD001	Width over cab 2240.0
Frame mm	
TD009	Frame width at front 945.0
TD010	Frame width at the rear 765.0
TD078	Frame profile 270 x 85 x 9,5
Heights mm	
TD033	Maximum external height, unladen 3311.0
TD082	Total transport height, unladen 3311.0
TD034	Maximum external height, laden 3213.0
TD035	Frame height at theoretical rear wheelbase, unladen 1140.0
TD036	Frame height at theoretical rear wheelbase, laden 1056.0
TD045	Raising from driving position, front 0.0
TD046	Lowering from driving position, front 0.0
TD047	Raising from driving position, rear 0.0
TD048	Lowering from driving position, rear 0.0
TD051	Height of fifth-wheel coupling above ground, unladen -
TD052	Height of fifth-wheel coupling above ground, laden -
Circle dimensions m	
TD055	Track circle diameter 19.6
TD056	Wall-to-wall turning circle diameter 21.4
Weights/loads kg	
TD026	Chassis weight with cab Error: 204
TD027	Chassis weight, front ---
TD028	Chassis weight, rear ---

TD029	Payload	---
TD018	Statutorily permissible gross vehicle weight	28000
TD025	Technically permissible gross vehicle weight	32500
TD031	Statutorily permissible gross train weight	0
TD032	Statutorily permissible trailer load	0

The technical data must be considered as an approximation. Some of the values are given in a simplified form. More detailed notes and descriptions can be found in the respective information in the overview. Contents and specifications have been compiled with the greatest possible care. Nevertheless, we do not assume responsibility for the data and values supplied being correct and up to date. Subject to errors and changes. MAN Truck & Bus AG is liable only in cases of intent, gross negligence or culpable breach of significant contractual obligations.



Information data - CO2-emissions

Information data - CO2-emissions

Vehicle	TGS 33.400 6x4 BB CH
Vehicle class	
Vehicle group	
Vehicle subgroup	
Simulation tool version	

005-20006-DAT_NOT_CO2_RELEVANT

There is no valid legislation for this vehicle configuration, which indicates CO2 emission data.