

Vehicle description for: TGS 33.440 6x6 BB CH

Vehicle standards

Product family	The new MAN Truck Generation
Model & Variant	TGS 33.440 6x6 BB CH
Vehicle type	Vehicle type, platform truck and chassis (LK)
Cab	Local transport cab NN
Main wheel distance	4500 mm
Overhang	2500 mm
Steering configuration	Left

Vertical Load

	National Registration	Technical Load	Technical Load Plus
Gross weight	29,000 kg	29,000 kg	29,000 kg
Front axle	9,000 kg	9,000 kg	9,000 kg
Rear axle	10,500 kg	10,500 kg	10,500 kg
Rear axle 2	10,500 kg	10,500 kg	10,500 kg

Horizontal Load

	National Registration	Technical Load	Technical Load Plus
Gross train weight	0 kg	0 kg	0 kg

The printed images in this offer are for explanatory purposes and may differ from the actual configuration.
 For further product information on the tire selection "selectively", please contact our sales staff.

Vehicle characteristics

Basic characteristics

<input type="checkbox"/>	Chassis	0P2U9
<input type="checkbox"/>	Chassis class, heavy	0P2UC
<input type="checkbox"/>	Merchant tonnage 33 t	0P8LK
<input type="checkbox"/>	Basic layout of vehicle, all-round	0PGCU
<input type="checkbox"/>	Frame type, high	0P2TP
<input type="checkbox"/>	Vehicle type, platform truck and chassis (LK)	0P2UQ
<input type="checkbox"/>	Left-hand-drive	0P3AS
<input type="checkbox"/>	Right-hand traffic	0P3F5
<input type="checkbox"/>	Vehicle documents in English	0P2L7
<input type="checkbox"/>	Labelling in English	0P8NM
<input type="checkbox"/>	Cab position 720 mm (distance from frame lower edge to cab floor)	0PHBF

Registration

<input type="checkbox"/>	Vehicle approval, N3G class	0P3JS
<input type="checkbox"/>	Maximum speed limiter, 85 km/h, electronic, engine speed regulation	0P2UI
<input type="checkbox"/>	Maximum vehicle noise level not defined	0P2YN
<input type="checkbox"/>	Height over cab, unloaded up to 4,000 mm	0PHA1
<input type="checkbox"/>	Maximum vehicle width of 2,500 mm checked with respect to relevant chassis components	0PIOJ
<input type="checkbox"/>	Vehicle classification in accordance with regulation (EU) 2018/858	0PKAW

Documents

<input type="checkbox"/>	European standard exhaust emission confirmation	0P2Q7
<input type="checkbox"/>	Without registration documentation, national	0P3B0
<input type="checkbox"/>	Special confirmation, heavy load / municipal operation	0P3CK
<input type="checkbox"/>	Cabling, in accordance with ADR	0P0YW

Application scope / transport tasks

<input type="checkbox"/>	Vehicle version municipal/public service deployment	0P0H7
<input type="checkbox"/>	Construction	0P6WH
<input type="checkbox"/>	Increase of the tyre load capacity by 10% (for communal supplement)	0P0UU
<input type="checkbox"/>	999 Miscellaneous vehicle	0P2S2
<input type="checkbox"/>	Temperature range, vehicle deployment, warm country	0PHIB
<input type="checkbox"/>	Case hardness of final drive Distribution	0P4F0

Lines, editions and packages

<input type="checkbox"/>	Special request paintwork	0PJTD
<input type="checkbox"/>	Without Individual Lion package	0PJT1

Horizontal and vertical loads

<input type="checkbox"/>	29,000 kg permitted gross load, vertical, nat. appr.	0P5QB
<input type="checkbox"/>	29,000 kg permitted gross load, vertical, tech.	0P5T1
<input type="checkbox"/>	29,000 kg permitted gross load, vertical, tech. Plus	0P8HP

<input type="checkbox"/>	9,000 kg permitted load on front axle, nat. appr.	0P5KX
<input type="checkbox"/>	9,000 kg permitted load on front axle, tech.	0P5LR
<input type="checkbox"/>	9,000 kg permitted load on front axle, tech. Plus	0P8EA
<input type="checkbox"/>	10,500 kg permitted load on rear axle NatZu	0P5GZ
<input type="checkbox"/>	10,500 kg permitted load on rear axle, tech.	0P5IB
<input type="checkbox"/>	10,500 kg permitted load on rear axle, tech. Plus	0P8BC
<input type="checkbox"/>	10,500 kg permitted load on 2nd rear axle NatZu	0P5FG
<input type="checkbox"/>	10,500 kg permitted load on 2nd rear axle, tech.	0P5M3
<input type="checkbox"/>	10,500 kg permitted load on 2nd rear axle, tech. Plus	0P7TA
<input type="checkbox"/>	0kN D value	0P8XD

Notification texts

<input type="checkbox"/>	Note: Restricted steerability with engaged differential lock on front axle	0PFZN
<input type="checkbox"/>	Note: Max. 42,000 kg tech. permitted gross weight with engaged off-road reduction ratio in transfer case	0PFZS
<input type="checkbox"/>	Increased. Wear and reduction in service life of propshafts, regular checks necessary	0PJRU

Chassis

Vehicle frame (wheelbase, overhang, ...)

<input type="checkbox"/>	Main wheelbase, 4,500 mm	0P2ZW
<input type="checkbox"/>	Wheelbase between rear axles, 1,400 mm	0P3BX
<input type="checkbox"/>	Frame overhang, rear, 2,500 mm	0P3E1
<input type="checkbox"/>	Main frame side member thickness, 9.5 mm	0P0Y7
<input type="checkbox"/>	Vehicle rear, straight end of frame	0P0XT

Exhaust system, air intake

<input type="checkbox"/>	Exhaust silencer, vertical, right	0P1BK
<input type="checkbox"/>	Exhaust tailpipe, behind cab, right, vertical, with outlet valve	0P1BN
<input type="checkbox"/>	Air intake, behind cab, raised	0P0AY
<input type="checkbox"/>	Pre-separator for engine air intake	0P0BA

Battery cases, batteries, alternator

<input type="checkbox"/>	Battery, 12 V, 175 Ah, 2 units, maintenance free	0P0WA
<input type="checkbox"/>	Alternator, Basic	0P1BV
<input type="checkbox"/>	Medium battery box, 2 batteries	0P0WU
<input type="checkbox"/>	Battery box, left	0P0WO
<input type="checkbox"/>	Main battery switch, mechanical	0P0WF
<input type="checkbox"/>	Fuses	0P1V1

Tanks and fuel line

<input type="checkbox"/>	Fuel tank capacity 400 l, right	0P4ED
<input type="checkbox"/>	Fuel tank, right, steel	0P4GN
<input type="checkbox"/>	Tank cross-section, right, medium	0P4HE
<input type="checkbox"/>	Fuel tank cap, lockable for master key system	0P4H5
<input type="checkbox"/>	Fuel pre-filter position on the battery box	0PIW9

Frame attachments

<input type="checkbox"/>	Without underride protection, front	0P1FM
--------------------------	-------------------------------------	-------

<input type="checkbox"/>	Without working platform	0P0VH
<input type="checkbox"/>	Without underride protection, side	0P1FG
<input type="checkbox"/>	Spare wheel, provisionally mounted	0P1GR
<input type="checkbox"/>	Final cross member, with hole pattern 160 x 100 mm	0P1SB
<input type="checkbox"/>	Without underride protection, rear	0P1FB
<input type="checkbox"/>	Wheel chock, 1 unit, with retaining device	0P1FO
<input type="checkbox"/>	Without body attachment brackets/thrust plates	0P0X6

Pneumatic brakes, compressed-air generation, brake system

<input type="checkbox"/>	Air compressor, 1-cylinder, 360 ccm	0P0AF
<input type="checkbox"/>	Compressed-air treatment, pneumatically controlled	0P0AB
<input type="checkbox"/>	Steel compressed-air tank	0P0XH
<input type="checkbox"/>	Electronic brake system (EBS)	0P0BL
<input type="checkbox"/>	Anti-lock braking system (ABS), Offroad, with additional off-road logic	0P0BF
<input type="checkbox"/>	Full brake assistant	0P0CM
<input type="checkbox"/>	Without preparation for EBS Full control unit	0PHPM
<input type="checkbox"/>	MAN EVB high-performance engine brake	0P0BV
<input type="checkbox"/>	Drum brakes on front axle	0P1IA
<input type="checkbox"/>	Drum brakes on rear axle	0P1I5
<input type="checkbox"/>	Drum brakes on 2nd rear axle	0P1IF
<input type="checkbox"/>	Parking brake control, next to driver's seat	0P3KH
<input type="checkbox"/>	Brake cylinder with parking brake for increased gross weight	0P8QF
<input type="checkbox"/>	Parking brake with spring-type actuator on rear axles (incl. leading axle/ trailing axle)	0PGBL
<input type="checkbox"/>	Hill-climbing brake braking function	0P1TD

Lights and acoustic signals on the chassis (rear lights, ...)

<input type="checkbox"/>	Rear lights	0P2AQ
<input type="checkbox"/>	Protective cover for rear lights	0P6XS
<input type="checkbox"/>	Acoust. Reversing warning system deactivatable when reverse gear selected	0P3CE
<input type="checkbox"/>	Light function test	0P2AD
<input type="checkbox"/>	Side marker lights, LED	0P2BJ

Driveline/running gear

Engine, radiator

<input type="checkbox"/>	Diesel engine MAN D2676 LF04, 324 kW (440 hp) output, 2,100 Nm torque, Euro 2	0P6BP
<input type="checkbox"/>	Fuel filter, for fuels up to Cleanliness Class 25	0PHII
<input type="checkbox"/>	Fuel pre-filter, with oil separator/water trap	0P0AT
<input type="checkbox"/>	Without torque reduction	0P0G5
<input type="checkbox"/>	Engine dry-air filter, with safety insert	0P0B8
<input type="checkbox"/>	Ventilation, crankcase, closed	0P8PM
<input type="checkbox"/>	Fan control for start of cooling with low coolant temperature (e.g. hot country)	0P0K5
<input type="checkbox"/>	Reduction of dust swirl through radiator fan	0P1YE
<input type="checkbox"/>	Engine cooler, extended	0P4XY
<input type="checkbox"/>	Radiator protection, lower	0P1XE
<input type="checkbox"/>	Front radiator protection, grille	0P1VP
<input type="checkbox"/>	Engine oil dipstick and digital oil level gauge	0P0B6
<input type="checkbox"/>	Warning message for engine coolant level, with advance warning	0P0KA

- | | |
|---|-------|
| <input type="checkbox"/> Antifreeze, down to -32 °C | 0P0AK |
| <input type="checkbox"/> Service product level indicator and intake system vacuum | 0P3KT |

Gearbox, clutch

- | | |
|--|-------|
| <input type="checkbox"/> Manually operated gearbox, MAN 16.25 OD | 0P5VL |
| <input type="checkbox"/> Gearbox for increased percentage of overrun during driving operation | 0PGCL |
| <input type="checkbox"/> Manual gearbox operation, single-H, group/split switch | 0P3KL |
| <input type="checkbox"/> Transfer case MAN G173 with on-road and off-road gear, neutral position | 0P4XK |
| <input type="checkbox"/> Transfer case lock management, electronic (VSM) | 0P0FU |
| <input type="checkbox"/> Single-disc clutch, 430 mm, dry, reinforced (LongLife) | 0P0DW |

Wheels, tyres

- | | |
|--|-------|
| <input type="checkbox"/> Required tyre speed index G | 0PFWA |
| <input type="checkbox"/> Tyres front axle Michelin 14.00R20 XZL+ off-road TL | 0PFB4 |



- | | |
|---|-------|
| <input type="checkbox"/> Rim type, front axle, steel, split | 0P0OZ |
| <input type="checkbox"/> Rim size, front axle, 10-hole, 10.00W-20 | 0P0NA |
| <input type="checkbox"/> Rear axle tyres Michelin 14.00R20 XZL+ Off-road TL | 0PDVC |



- | | |
|--|-------|
| <input type="checkbox"/> Rim type, rear axle, steel, split | 0P0ON |
| <input type="checkbox"/> Rim size, rear axle, 10-hole, 10.00W-20 | 0P0MM |
| <input type="checkbox"/> Tyres for 2nd rear axle Michelin 14.00R20 XZL+ Offroad TL | 0PEDC |



- | | |
|--|-------|
| <input type="checkbox"/> Rim type, 2nd rear axle, steel, split | 0P0P9 |
| <input type="checkbox"/> Rim size, 2nd rear axle, 10-hole, 10.00W-20 | 0P0NZ |
| <input type="checkbox"/> Spare wheel, in accordance with configuration for rear axle tyres | 0P0MF |

Axles

- | | |
|--|-------|
| <input type="checkbox"/> 6x6 | 0P3BD |
| <input type="checkbox"/> Steering ratio, indirect | 0P1JY |
| <input type="checkbox"/> Steering oil tank with electrical measuring sensor | 0P1JV |
| <input type="checkbox"/> Front axle, 9,000 kg, planetary axle without drive shaft, straight, steered, not liftable | 0P5ES |
| <input type="checkbox"/> Front axle as planetary axle, driven, permanent | 0P1GX |
| <input type="checkbox"/> Mudguard, front axle | 0P1AT |
| <input type="checkbox"/> Rear axle, 13,000 kg, planetary axle with drive shaft, straight, not steered, not liftable | 0P4ZM |
| <input type="checkbox"/> Single tyre on rear axle | 0P1HM |
| <input type="checkbox"/> Mudguard, rear axle, plastic half shells in front of rear axle | 0P1AO |
| <input type="checkbox"/> 2nd rear axle, 13,000 kg, planetary axle without drive shaft, straight, not steered, not liftable | 0P4Y7 |
| <input type="checkbox"/> Single tyre on 2nd rear axle | 0P1HV |
| <input type="checkbox"/> Mudguard, plastic half shells, behind 2nd rear axle | 0P1AX |
| <input type="checkbox"/> Splash guard mat on mudguard, 2nd rear axle | 0P1XY |
| <input type="checkbox"/> Axle ratio, $i = 5.33$ | 0P0DD |
| <input type="checkbox"/> Differential locks on driven rear axles | 0P0DI |
| <input type="checkbox"/> Differential locks on driven front axles | 0P0DK |
| <input type="checkbox"/> Warning buzzer when front axle locks are engaged | 0P0DQ |
| <input type="checkbox"/> Mudguard enlargement | 0P1W5 |

Axle control system and suspension

- | | |
|--|-------|
| <input type="checkbox"/> Suspension type for front axles and driven rear axles, leaf/leaf (BB) | 0P2YB |
| <input type="checkbox"/> Leaf-spring suspension on front axle, parabolic, 3-leaf, steel | 0P1JE |
| <input type="checkbox"/> Leaf-spring suspension on rear axle, parabolic, 5-leaf, steel | 0P1J2 |
| <input type="checkbox"/> Leaf-spring suspension on 2nd rear axle, parabolic, 5-leaf, steel | 0P1JL |
| <input type="checkbox"/> Spring load-bearing capacity front axle 9,500 kg | 0P5C4 |

<input type="checkbox"/>	Spring load-bearing capacity of rear axle, 13,000 kg	0P5BV
<input type="checkbox"/>	Spring load-bearing capacity of 2nd rear axle, 13,000 kg	0P5C7
<input type="checkbox"/>	Shock absorbers on front axle	0P1M4
<input type="checkbox"/>	Shock absorbers on rear axle	0P1LQ
<input type="checkbox"/>	Shock absorbers on 2nd rear axle	0P1M9
<input type="checkbox"/>	Stabiliser, front axle	0P1LD
<input type="checkbox"/>	Stabiliser, rear axle	0P1LA
<input type="checkbox"/>	Stabiliser, 2nd rear axle	0P1LH
<input type="checkbox"/>	Wishbone, reinforced	0P6ZS

Cab

Cab and cab exterior

<input type="checkbox"/>	Local transport cab NN	0P2DL
<input type="checkbox"/>	Cab mount, Basic	0P1V8
<input type="checkbox"/>	Cab tilt mechanism, manual	0P1V6
<input type="checkbox"/>	No tilting roof/sliding roof	0P1VY
<input type="checkbox"/>	Bumper, steel, 3 pieces	0P1SG
<input type="checkbox"/>	Front step, integrated, with grab option	0P1VE
<input type="checkbox"/>	Windscreen, composite safety glass, tinted	0P1X0
<input type="checkbox"/>	Sunblind, in front of windscreen	0P1WK
<input type="checkbox"/>	Wiper system for windscreen	0P1WG
<input type="checkbox"/>	Wiper activation, manual	0P1UL
<input type="checkbox"/>	Step unit, hinged	0P1V0
<input type="checkbox"/>	Central locking, no remote control	0P1WS
<input type="checkbox"/>	Vehicle key, 2 units	0P3JT
<input type="checkbox"/>	No door extension	0P1WV
<input type="checkbox"/>	Door labelling, according to trade tonnage of vehicle	0P2DQ
<input type="checkbox"/>	Door windows, tinted	0P1WO
<input type="checkbox"/>	Door window, safety glass	0P1WM
<input type="checkbox"/>	Cab rear wall, no window	0P1VD

Lights and acoustic signals on cab exterior (headlights, horn, ...)

<input type="checkbox"/>	Front headlights, H7	0P1ZN
<input type="checkbox"/>	Stone protection guard for front headlights, wide and fine mesh	0PICD
<input type="checkbox"/>	Daytime driving lights, H7	0P2BN
<input type="checkbox"/>	Fog lights, H7	0P2AH
<input type="checkbox"/>	Headlight beam regulator, manual	0P2AC
<input type="checkbox"/>	Driving-light control, manual	0P1ZF
<input type="checkbox"/>	Contour lights, LED, 2 units	0P2BS
<input type="checkbox"/>	Turn signal lights, sides, bulb	0P1Z6
<input type="checkbox"/>	Horn, two-tone, electrical	0P1W1
<input type="checkbox"/>	Revolving beacons, LED, yellow (individual LEDs light up in cascades, revolving)	0P2BD
<input type="checkbox"/>	Revolving beacon on cab roof, left	0P2B1
<input type="checkbox"/>	Spotlight, 1 unit, cab roof, left	0P1YK
<input type="checkbox"/>	Spotlight, LED, white	0PJQA
<input type="checkbox"/>	Switch for spotlight/manoeuvring light	0P5U5
<input type="checkbox"/>	Preparation for loading area lighting	0P2A5

- | | |
|---|-------|
| <input type="checkbox"/> Without revolving beacons at the rear of the vehicle | 0PJRO |
|---|-------|

Mirrors and mirror replacements

- | | |
|---|-------|
| <input type="checkbox"/> Exterior rear-view mirror, mechanically adjustable | 0P2CC |
| <input type="checkbox"/> Mirror housing, not painted | 0P2CP |
| <input type="checkbox"/> Vehicle components, suitable for body width larger than 2,400 mm to 2,600 mm | 0P2CT |
| <input type="checkbox"/> Kerb mirror, right, mechanically adjustable | 0P2CH |
| <input type="checkbox"/> Front mirror, mechanical adjustment | 0P2CJ |

Seats

- | | |
|--|-------|
| <input type="checkbox"/> Seat covers, fabric, standard | 0P2PQ |
| <input type="checkbox"/> Comfort driver's seat, air-sprung | 0P2P2 |
| <input type="checkbox"/> Co-driver's seat, not sprung, with storage box | 0P2OO |
| <input type="checkbox"/> Storage space, in seat bracket of co-driver's seat | 0P2Q6 |
| <input type="checkbox"/> Middle seat, folding backrest, 2-point seatbelt | 0P2PG |
| <input type="checkbox"/> Seat belt indicator, driver's side, acoustic and visual | 0P2NB |

Driver's workplace

- | | |
|--|-------|
| <input type="checkbox"/> Steering wheel, adjustable height and angle | 0P2GB |
| <input type="checkbox"/> Steering wheel, with parking position | 0P2GE |
| <input type="checkbox"/> Steering lock | 0P3JZ |
| <input type="checkbox"/> Instrumentation, Basic km/h | 0P3L3 |
| <input type="checkbox"/> Tachograph Simulation Unit (TSU), instead of tachograph | 0P2KY |
| <input type="checkbox"/> Tachograph, calibrated | 0P2KG |
| <input type="checkbox"/> Socket, cab centre, 2 units, 12 V and 24 V | 0P2HX |
| <input type="checkbox"/> Standard control field, inside of driver's door, with door open operated externally, 4 function buttons | 0P3KE |
| <input type="checkbox"/> Single DIN slots, 4 units, roof space, front | 0P2FJ |

Cab air-conditioning system

- | | |
|---|-------|
| <input type="checkbox"/> Air-conditioning system, manual | 0P2NU |
| <input type="checkbox"/> Pre-separator (cyclone filter) for interior air intake | 0P2O7 |

Bunk area

- | | |
|--|-------|
| <input type="checkbox"/> Without bunk area package | 0PKNE |
|--|-------|

Cab interior

- | | |
|---|-------|
| <input type="checkbox"/> Without interior lighting package | 0PKNF |
| <input type="checkbox"/> Colour scheme for interior styling, dark | 0P2I6 |
| <input type="checkbox"/> Interior styling analogous to colour scheme | 0PGBT |
| <input type="checkbox"/> Windscreen roller blind, internal | 0P2FE |
| <input type="checkbox"/> Interior light, central | 0PHA6 |
| <input type="checkbox"/> Entry lighting | 0P2IO |
| <input type="checkbox"/> Door interior cladding, washable | 0P2IA |
| <input type="checkbox"/> Storage, instrument panel in middle section, open | 0P2HK |
| <input type="checkbox"/> 2 storage compartments, cab rear wall, behind driver's and co-driver's side and net on cab rear wall | 0PGB8 |
| <input type="checkbox"/> Grab handle, above door, internal, 2 units, 1 right and 1 left | 0P2G2 |
| <input type="checkbox"/> Entry handles, standard | 0PHPK |

Accessories and tools

<input type="checkbox"/>	Jack, 12,000 kg	0P3F8
<input type="checkbox"/>	Vehicle toolkit	0P2TX
<input type="checkbox"/>	No warning triangle	0P3FH
<input type="checkbox"/>	Operator's manual in English, printed, additional	0P2JB

Intelligent Truck

Assistance systems

<input type="checkbox"/>	Without advanced emergency braking system	0P1U5
--------------------------	---	-------

Infotainment (radio,...)

<input type="checkbox"/>	MMT infotainment system, Starter Basic	0P2M1
<input type="checkbox"/>	MAN Advanced sound system	0P2MH
<input type="checkbox"/>	No navigation map	0P2N2

Bodies/interfaces

Interfaces to semitrailer (e.g. fifth-wheel coupling, brake connection,...)

<input type="checkbox"/>	Without trailer brake connection behind cab	0P1O3
<input type="checkbox"/>	No fifth-wheel coupling	0P1RJ

Interfaces to trailer (e.g. trailer coupling, brake connections,...)

<input type="checkbox"/>	Without trailer/towing coupling on final cross member	0P1NQ
<input type="checkbox"/>	Preparation for trailer coupling on final cross member	0P1SQ
<input type="checkbox"/>	Without trailer brake connection at end of frame, centre	0P1O0
<input type="checkbox"/>	Without trailer socket at frame end	0P1OW
<input type="checkbox"/>	Without trailer socket for anti-lock brake system (ABS)	0P1O9

Ex works bodies and interfaces to bodies (e.g. tipper indicator,...)

<input type="checkbox"/>	Interface for data exchange with body (DIN), behind cab	0P2N8
--------------------------	---	-------

PTOs

<input type="checkbox"/>	PTO, gearbox-dependent, type NH/4c, without flange, $f=1.17/1.40$, position approx. 3 o'clock	0P4QI
<input type="checkbox"/>	PTO, gearbox-dependent, for short-time operation less than 60 min	0P4VK
<input type="checkbox"/>	PTO, gearbox-dependent, shiftable	0P4X9
<input type="checkbox"/>	Without fan wheel for PTO, gearbox-dependent	0P4VR
<input type="checkbox"/>	Function parameters for PTO, gearbox-dependent, stationary operation	0P4WO
<input type="checkbox"/>	Gearbox shift blocking for PTO operation, pneumatic	0P4VS
<input type="checkbox"/>	Sector-specific parameterisation for high-power PTOs/ severe load alteration (working speed control)	0PJBC

Towing, recovery and lashing

<input type="checkbox"/>	Central coupling jaw, integrated in bumper/front cross member, with lock pin	0P1MK
<input type="checkbox"/>	Shackles, 2 units, front of vehicle	0P1S3

Paintworks

Paintwork, cab, top

<input type="checkbox"/>	Top coating, cab	0P6YB
--------------------------	------------------	-------

Paintwork, cab, bottom

<input type="checkbox"/>	Textured coating, step units	0P6X9
<input type="checkbox"/>	Textured coating, mudguard, behind cab	0P6YG
<input type="checkbox"/>	Textured coating, bumper, steel	0P6YQ

Paintwork, chassis

<input type="checkbox"/>	Top coating, chassis	0P6YC
<input type="checkbox"/>	Top coating, rims, steel, white-aluminium	0P6YL

Additional operating equipment

<input type="checkbox"/>	Eintrag in KFZ-Brief: Anhängelast 40.000kg bei Zgg. 59.000kg	ZW001
--------------------------	--	-------

Colour

<input type="checkbox"/>	Top coating, cab	PURE WHITE RAL 9010	N
<input type="checkbox"/>	Top coating, chassis	GRAPHITE BLACK RAL 9011	W

Technical data: TGS 33.440 6x6 BB CH / L56EAA04

Vehicle type: Vehicle type, platform truck and chassis (LK)		TD028	Chassis weight, rear	4712
Cab: Local transport cab NN		TD029	Payload	18637
Drive Type: 6x6		TD018	Statutorily permissible gross vehicle weight	29000
		TD025	Technically permissible gross vehicle weight	29000
		TD031	Statutorily permissible gross train weight	0
		TD032	Statutorily permissible trailer load	0
Lengths		mm		
TD071	Total length	10007.0		
TD063	Front vehicle overhang	1607.0		
TD057	Wheelbase between front axles	0		
TD058	Wheelbase between leading axle and rear axle	0		
TD059	Wheelbase between rear axles	1400		
TD060	Wheelbase between rear axle and trailing axle	0		
TD064	Rear frame overhang	2500.0		
TD072	Distance from first front axle to body	830.0		
TD067	Distance to kingpin from front axle, nominal position	-		
TD074	Slew radius, front	-		
TD075	Slew radius, rear	-		
TD068	Coupling length	-		
Widths		mm		
TD008	Width included rearview mirror	2981.0		
TD001	Width over cab	2240.0		
Frame		mm		
TD009	Frame width at front	945.0		
TD010	Frame width at the rear	765.0		
TD078	Frame profile	270 x 85 x 9,5		
Heights		mm		
TD033	Maximum external height, unladen	3500.0		
TD082	Total transport height, unladen	3500.0		
TD034	Maximum external height, laden	3402.0		
TD035	Frame height at theoretical rear wheelbase, unladen	1258.0		
TD036	Frame height at theoretical rear wheelbase, laden	1178.0		
TD045	Raising from driving position, front	0.0		
TD046	Lowering from driving position, front	0.0		
TD047	Raising from driving position, rear	0.0		
TD048	Lowering from driving position, rear	0.0		
TD051	Height of fifth-wheel coupling above ground, unladen	-		
TD052	Height of fifth-wheel coupling above ground, laden	-		
Circle dimensions		m		
TD055	Track circle diameter	Error: 204		
TD056	Wall-to-wall turning circle diameter	Error: 204		
Weights/loads		kg		
TD026	Chassis weight with cab	10363		
TD027	Chassis weight, front	5651		

The technical data must be considered as an approximation. Some of the values are given in a simplified form. More detailed notes and descriptions can be found in the respective information in the overview. Contents and specifications have been compiled with the greatest possible care. Nevertheless, we do not assume responsibility for the data and values supplied being correct and up to date. Subject to errors and changes. MAN Truck & Bus AG is liable only in cases of intent, gross negligence or culpable breach of significant contractual obligations.